

Package: centr (via r-universe)

November 30, 2024

Title Weighted and Unweighted Spatial Centers

Version 0.2.0

Description Generate mean and median weighted or unweighted spatial centers. Functions are analogous to their identically named counterparts within 'ArcGIS Pro'. Median center methodology based off of Kuhn and Kuenne (1962)
<doi:10.1111/j.1467-9787.1962.tb00902.x>.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Imports sf

URL <https://ryanzomorrodi.github.io/centr/>,
<https://github.com/ryanzomorrodi/centR>

Suggests data.table, knitr, rmarkdown, testthat (>= 3.0.0), tibble, tidycensus

Config/testthat/edition 3

BugReports <https://github.com/ryanzomorrodi/centR/issues>

VignetteBuilder knitr

Config/pak/sysreqs libgdal-dev gdal-bin libgeos-dev libssl-dev
libproj-dev libsqlite3-dev libudunits2-dev

Repository <https://ryanzomorrodi.r-universe.dev>

RemoteUrl <https://github.com/ryanzomorrodi/centr>

RemoteRef HEAD

RemoteSha 292917c2da3b1209cf8814a696564ceeb8fa7870

Contents

mean_center	2
median_center	3

 mean_center

Mean Center

Description

Mean center calculates the geographic average center. One can specify the groups to calculate individual centers for groups and weights for each individual point. It is analagous to the [ArcGIS Pro Mean Center](#) tool.

If `st_is_longlat(x)`, mean center is calculated assuming a spherical Earth. Projected data is calculated assuming a "flat" Earth.

Usage

```
mean_center(x, group = NULL, weight = NULL)
```

Arguments

<code>x</code>	Input POINT or POLYGON simple features
<code>group</code>	name of character column specifying groups to calculate individual mean centers for
<code>weight</code>	name of numeric weight column specifying an individual point's contribution to the mean center

Value

An sf object with a mean center for each group

Examples

```
df <- data.frame(
  lon = c(20, 50, 30, 80, 10),
  lat = c(25, 70, 30, 50, 30),
  grp = c("a", "b", "a", "b", "a"),
  wt = c(1, 5, 1, 3, 2)
)
x <- sf::st_as_sf(df, coords = c("lon", "lat"), crs = 4326)
mean_center(x, group = "grp", weight = "wt")
```

median_center	<i>Median Center</i>
---------------	----------------------

Description

Median center iteratively calculates the point that minimizes distance to all features. One can specify the groups to calculate individual centers for and weights for each individual point. It is analogous to the [ArcGIS Pro Median Center](#) tool.

It uses the methodology introduced by Kuhn and Kuenne (1962).

Currently, median center is only implemented for projected data.

Usage

```
median_center(x, group = NULL, weight = NULL, tolerance = 1e-04)
```

Arguments

x	Input POINT, MULTIPOINT, POLYGON, or MULTIPOLYGON simple features
group	name of character column specifying groups to calculate individual median centers for
weight	name of numeric weight column specifying an individual point's contribution to the median center
tolerance	numeric threshold determining when an estimate improvement is sufficiently small enough to stop iterating (smaller = slower, but more precision)

Value

An sf object with a median center for each group

Examples

```
df <- data.frame(
  lon = c(-88, -90, -92, -89, -90),
  lat = c(42, 40, 30, 32, 42),
  grp = c("a", "b", "a", "b", "a"),
  wt = c(1, 1, 1, 1, 1)
)
x <- sf::st_as_sf(df, coords = c("lon", "lat"), crs = 4326)
x_transformed <- sf::st_transform(x, crs = "ESRI:102003")
median_center(x_transformed, group = "grp", weight = "wt")
```

Index

`mean_center`, [2](#)
`median_center`, [3](#)